

## Product Specification Sheet



### VideoXtreme Projectors VX-11d

Specification	Detail
<b>Projector Type</b>	Digital Light Processing™ (DLP),™ 3-Chip, SuperOnyx™ DMD™
<b>Native Resolution</b>	Full HD, 1920 x 1080
<b>Aspect Ratios</b>	16:9, 4:3, Letterbox, VirtualWide, Cinema, VirtualCinema as determined by video processor
<b>Video Standards</b>	NTSC, PAL, SECAM, CEA-861D DTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i 50/60, 1080p 24/50/60
<b>Standard-Lens:</b>	
<b>Optional Lens:</b>	Proteus 1: Fixed 0.77:1 (for rear-screen application) Proteus 2: Zoom 1.45 - 1.74:1 (with CineWide McKinley 1.09 - 1.31:1) Proteus 3: Zoom 1.82 - 2.24:1 (with CineWide McKinley 1.30 - 1.63:1) Proteus 4: Zoom 2.17 - 2.90:1 (with CineWide McKinley 1.63 - 2.17:1) Proteus 5: Zoom 2.90 - 4.34:1 (with CineWide Rainer 2.17 - 3.26:1) Proteus 6: Zoom 4.34 - 6.76:1 (with CineWide Rainer 3.26 - 5.07:1)
<b>Lens-Shift (Offset)</b>	<b>Vertical:</b> Up to 65% of image height down or up from screen center <b>Horizontal:</b> Up to 30% of image width left or right from screen center (Proteus 1 has no offset capabilities)
<b>Light Output</b>	2100 ANSI Lumens; CSMS Specifications: Home Theater Calibration: 1845 ANSI Lumens; 119 Foot-Lamberts (fL); 2100 Ansi Lumens (uncalibrated)
<b>Contrast Ratio</b>	CSMS Contrast Ratio: >250:1(Ansi); 10000:1 full-on, full-off (dynamic)
<b>Lamp</b>	230/260W (selectable) HPM lamp
<b>Lamp life</b>	2000/3000 hours typical (Standard/Economy Mode)
<b>Inputs</b>	See DHD4 Processor Specs
<b>Power Requirements</b>	100V-240V VAC +/- 10% @ 50/60Hz < 400W maximum
<b>Operating Environments</b>	Temperature: 50-104 °F (10-40 °C) Humidity: 0-85% relative humidity (non-condensing)
<b>Regulatory Approvals</b>	FCC Part 15 Class B, CE Class B, UL, cUL, CB, RoHS, WEEE, local conformances as required
<b>12V Output</b>	
<b>Picture Size (16:9 Screens)</b>	Recommended Width: 72" - 120" (183 - 305 cm) Maximum Width: 180" (457 cm)
<b>Dimensions</b>	Width: 21.13 in. (537 mm) Height: 8.25 in. (235 mm) without feet Depth: 25.25 in. (641 mm)
<b>Lamp Warranty</b>	1000 hours or (6) Six months, whichever comes first
<b>Limited Warranty</b>	Projector: (2) Two years parts and labor from the date of shipment from Runco.
<b>Extended Warranty (Option)</b>	RuncoCare™, Red Carpet™, and PremierCare™ also available.
<b>Processor</b>	Runco DHD4 Processor with Vivix™ technology and single cable display connectivity
<b>Control</b>	RuncoLink, Ethernet, RS-232, IR remote
<b>Calibration</b>	IDF Certified Calibration Configuration
<b>Color Gamut</b>	> BT.709 (REC709)
<b>Lens System</b>	Motorized focus, zoom, vertical and horizontal offset

Specifications are subject to change without notice.

Specification Report Date: 1/20/2012